

JINDA PRODUCTS DATA SHEET



Code: 0411871
Name: PP60um(TC)/JT14D/30umClearPET

Facestock: **Gloss White PP**

Caliper:	60±4	um	TAPPI T411
Weight:	45+2	g/m ²	TAPPI T410
Gloss:	65	%	
Tensile Strength:	105	MD	ASTM D882
	185	CD	ASTM D882
Elongation at Break	170	MD	ASTM D882
	55	CD	ASTM D882

Roll Size:

Length:	500m-6000m
Full width:	1070mm

Printing / Converting

Applicable for letter press, flexo, offset, screen printing
Water based and UV inks are applicable
Testing prior to ink selection is always needed.
Roll tension should be controlled to avoid bleeding

Adhesive: **Solvent Glue JT14D**

Weight:	20±2	g/m ²	
Loop Tack:	≥15	N	FTM 9
Peel Adhes. 90°	≥10	N/25mm	FTM 2
Min. appl. Temp	5	°C	
Service temp.	-20 ~ 80	°C	

Stable and easy for die cut and dispense.
Suitable for a variety of labeling environment
Not recommend to apply on irregular substrates

Application

The product is suitable for a wide range of promotional and industrial label applications.
Especially for home & personal care labeling
Such as air-care, skin care, oral care, bath shower etc

Storage:

Two year since produce time when stored at 20℃
at 50% RH.Avoid direct sunlight and keep storage environment dry and ventilated,

Liner: **Clear PET 30um**

Weight:	42±2	g/m ²	ISO 536
Caliper:	30±5	um	ISO 534

It is primarily used for roll-to-roll label conversion and automatic labelling

Remark:

All statements, the technical information and recommendations about JINDA products are based upon tests believed to be reliable but do not constitute a guarantee or warranty.
The product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

JIANGSU JINDA PACKAGING MATERIALS TECHNOLOGY CO., LTD

NO. 196, YAOCHI MIDDLE ROAD, HAIAN CITY, NANTONG CITY, JIANGSU PROVINCE, CHINA
Email: jack@jdlable.com Tel: +86 15000182802

Last modified 2024.05