JINDA PRODUCTS DATA SHEET

JINDA
New choice,More value

Code: 0411216
Name: Gloss white PP 60um/AS500/60gwhite glassine liner

Facestock:	**Gloss White PP**		
Caliper:	60±4	um	TAPPI T411
Weight:	45+2	g/m²	TAPPI T410
Gloss:	65	%	
Tensile Strength:	105	MD	ASTM D882
	185	CD	ASTM D882
Elogation at Break:	170	MD	ASTM D882
	55	CD	ASTM D882

Roll Size:

Length:	500m-3000m
Full width:	1530mm

Printing / Converting

Applicable for letter press, flexo, offset, screen printing
Water based and UV inks are applicable
Testing prior to ink selection is always needed.
Roll tension should be controled to avoid bleeding

Adhesive:	**Acrylic AS500**		
Weight:	20±2	g/m²	
Loop Tack:	≥7	N	FTM 9
Peel Adhes. 90°	≥5	N/25mm	FTM 2
Min. appl. Temp	0	°C	
Service temp.	-20 ~ 80 °C		

Stable and easy for die cut and dispense.
Suitable for a variety of labeling environment
Not recommend to apply on irregular substrates

Application

The product is suitable for a wide range of promotional and industrial label applications
Especially for cosmetics and daily chemicals

Storage:

Two year since produce time when stored at 20°C at 50% RH.Avoid direct sunlight and keep storage environment dry and ventilated,

Liner:	**60g White Glassine**		
Weight:	60±2	g/m²	ISO 536
Caliper:	55±5	um	ISO 534
Trensparency:	50±3	%	DIN 53147

It is primarily used for roll-to-roll label conversion and automatic labelling

Remark:

All statements,thechnical information and recommendations about JINDA products are based upon tests believed to be reliable but do not constitute a guarentee or warranty.
The product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.