JINDA PRODUCTS DATA SHEET

JINDA
New choice,More value

Code: 0410131
Name: Thermal Transfer 70g/AJ900/60g white glassine liner

Facestock: Thermal Transfer 70g

Caliper:	87±6	um	TAPPI T411
Weight:	70+3	g/m²	TAPPI T410
Brightness:	85-87	%	TAPPI T525
Opacity:	90%	%	TAPPI T425

Roll Size:

Length:	500m-3000m
Full width:	1530mm

Printing / Converting

Applicable for Thermal transfer ribbon printing
letter press, flexo, offset, screen printing
Testing prior to ribbon selection is always needed.
Roll tension should be controled to avoid bleeding

Adhesive: Acrylic Aj900

Weight:	22±2	g/m²	
Loop Tack:	⩾12	N	FTM 9
Peel Adhes.	⩾14	N/25mm	FTM 2
Min. appl. Temp.	0	°C	
Service temp.	-20 ~ 80 °C		

Stable and easy for die cut and dispense.
Suitable for a variety of labeling environment
Not recommend to apply on irregular substrates

Application

The product is thermal transfer printable by ribbon.
It is mainly designed for barcode printing.
Multi-colors printing is also appicable.

Storage:

Two year since produce time when stored at 20°C at 50% RH.Avoid direct sunlight and keep storage environment dry and ventilated,

Liner: 60g White Glassine

Weight:	60±2	g/m²	ISO 536
Caliper:	55±5	um	ISO 534
Trensparency:	50±3	%	DIN 53147

It is primarily used for roll-to-roll label conversion and automatic labelling

Remark:

All statements,thechnical information and recommendations about JINDA products are based upon tests believed to be reliable but do not constitute a guarentee or warranty.
The product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.