1TP01B60 THERMAL TRANSFER PAPER-BP01-BG60

Face Paper:

A woodfree paper with an ultra-smooth surface, suitable for mid and high speed printer. It can provide fine performance in printing.

Base Weight:	68 g/m^2	GB/T451.2
Caliper:	70 um	GB/T451.3

Adhesive:

Permanent Rubber Base Hot Melt Adhesive

Liner:

A white Super calendered glassine with good internal strength and luminousness. It has characters of high-temperature, moisture and oil resistance. It is suitable for high- soeed auto labeling liner, printing & die-cutting desing. It has excellent performance in Die cutting processing.

Base Weight:	60 g/m2	GB/T451.2
Caliper:	53 um	GB/T451.3

Laminate:

Total Caliper:	140 um ±10%	GB/T451.3

Performance Data:

Loop Tack	15 20N	GB/T31125-2014
180°Peel Strength	7-8N/CM	GB/T2792
Min Apply Temperature	0°C	
Service Temperature	-40°C-65°C	

Adhesive Performance

A good performance and wide application permanent hot melt adhesive. The adhesive features excellent tack and adhesion on a wide variety of clean substrates like paper, metal, glass, PP/PE/PET, etc. under room temperature.

Application and use:

Compatibility with a wide range of wax, resin and wax-resin, thermal transfer ribbons. It has an excellent barcode print performance speed up to 14inch/s. Application include address, product and safety data labeling. It is not suggested to apply under cold environment.

Shelf life: 2 years at 23±2°C, RH 50%

Creation Date: March. 13, 2020

Version: B/05

Add: No. 405 Yuanshi St.,Shijiazhuang, 051134, China
Tel. +86-311-86538681 Fax: +86-311-86538685
www.fangdapack.com Email: sales@hbfd.cn