

**JINDA PRODUCTS DATA SHEET**

Code: 0403235  
Name: Woodfree 70g/AJ900/60g white glassine liner

**Facestock: Woodfree Paper**

|             |       |                  |            |
|-------------|-------|------------------|------------|
| Caliper:    | 82±8  | um               | TAPPI T411 |
| Weight:     | 70±3  | g/m <sup>2</sup> | TAPPI T410 |
| Brightness: | 85-87 | %                | TAPPI T525 |
| Opacity:    | 82    | %                | TAPPI T425 |

**Roll Size:**

|             |            |
|-------------|------------|
| Length:     | 500m-3000m |
| Full width: | 1530mm     |

**Printing / Converting**

Applicable for letter press, flexo, offset, screen printing  
Water based and UV inks are applicable  
Testing prior to ink selection is always needed.  
Roll tension should be controlled to avoid bleeding

**Adhesive: Acrylic Aj900**

|                  |             |                  |       |
|------------------|-------------|------------------|-------|
| Weight:          | 22±2        | g/m <sup>2</sup> |       |
| Loop Tack:       | ≥12         | N                | FTM 9 |
| Peel Adhes.      | ≥14         | N/25mm           | FTM 2 |
| Min. appl. Temp. | 0           | °C               |       |
| Service temp.    | -20 ~ 80 °C |                  |       |

Stable and easy for die cut and dispense.  
Suitable for a variety of labeling environment  
Not recommend to apply on irregular substrates

**Application**

The product is suitable for a wide range of promotional and office stationary labels applications, and price gun labels etc.

**Storage:**

Two year since produce time when stored at 20°C at 50% RH. Avoid direct sunlight and keep storage environment dry and ventilated,

**Liner: 60g White Glassine**

|               |      |                  |           |
|---------------|------|------------------|-----------|
| Weight:       | 60±2 | g/m <sup>2</sup> | ISO 536   |
| Caliper:      | 55±5 | um               | ISO 534   |
| Transparency: | 50±3 | %                | DIN 53147 |

It is primarily used for roll-to-roll label conversion and automatic labelling

**Remark:**

All statements, technical information and recommendations about JINDA products are based upon tests believed to be reliable but do not constitute a guarantee or warranty.  
The product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.